FEB 2 7 2007

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In the Application of: Vogel et al. CASE NO: AD6728 US NA

APPLICATION NO.: 09/833,452 GROUP ART UNIT: 1773

FILED: 04/12/2001 EXAMINER: Jackson, Monique R

FOR: Multi-Layered, Co-Extruded Ionomeric Decorative Surfacing

RULE 131 DECLARATION

Commissioner for Patents P.O. Box 1450 Alexandria VA 22313-1450

Sir:

I, Lori J. Pike, declare that:

I am a citizen of the United States of America residing in Newark, Dclaware;

I am a co-inventor of the above-identified application for US patent and have read the Office Action mailed 01/10/2007;

I have been employed by E. I. du Pont de Nemours & Company (DuPont) since June - 1981 as an engineer working in various areas of plant support, process engineering, and technical service and development of ethylene copolymers including polymers for film and sheet since 1985;

I made several runs of coextruded two layer films comprising ionomer Surlyn® film as top layer and another ionomer Surlyn® film as second layer well before December 15, 1998;

I had reduced my invention, before December 15, 1998, as described and claimed in the subject application in this country, evidenced by the following exhibits:

Exhibit A, attached hereto, is a photocopy of work request 710802 by me (L. Pike) and operated by Bruce Dennison and Earl Herriman as operators; two runs are shown on this Exhibit A (Sample number E203-56-51 and E203-56-2); the equipment employed was a coextruder located at DuPont's Chestnut Run facility in Wilmington, Delaware; the resins shown on the farthest left column of the request represents were Surlyn® 1706 (zinc ionomer) and Surlyn® 7930 (lithium ionomer), both were manufactured and sold by DuPont at that time; Exhibit A also shows that an additive CONPOL 5B10S1 was present in one of the

Application/Control Number: 09/833,452
Art Unit: 1712

Page 2

ionomer layers; CONPOL was used as antiblock and slip agent additive with different concentrations (0.05 wt % and 0.01 wt %) in the two runs;

Several other two layer films were also made similarly; for example, Exhibit B (work request 150405) shows four (4) two-layer runs (sample numbers E229-41-1, E229-41-2, E229-41-3, E229-41-4); each of runs E229-41-1 and E229-41-2 comprised Surlyn® 1601 film as top layer and another Surlyn® NWL film as second layer; each of run E229-41-3 and E229-41-4 comprised Surlyn® HT 2010 film as top layer and another Surlyn® NWL film as second layer; Surlyn® 1601 and Surlyn® NWL were each a sodium ionomer; Surlyn® HT 2010 was a high transparency sodium ionomer grade.

Not shown are more ionomer/ionomer two-layer runs carried out by me, but the above-illustrated two exhibits unequivocally demonstrate that I conceived and reduced to practice the invention claimed in the above-identified application before the filing date of the parent application of the Smith reference relied on by the examiner; and

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Lori I Pike

Date

opplication No. 09/833,452

ocket No. AD6728 US NA

FILM

BLOWN

ECORD

00

ATA

EXTRUSION




A

EXHIBIT

BEST AVAILABLE COPY

5 P. 48 Adaptor Air Temp PSI + Amt Chilled 853 ひ~しみからん (5 2730 280 1990 Ф В ĞΣ d 4 76 4 N SCREW SPEED RPM 0 G COURTER 0 9 -292 2/2" SATS MELT Temp. "F HEIGHT ANGLE TOWER Soot Cata ્રે SCREW J DIE 176 光 ゴ 7 435 1435 TOP DIE TEMP. °F (SET/READ) CENTER 435 435 DAVIS 357 Bottom 433 J 733 435 435 NECK J Adaptor 435 435 5 435 4% WELEX イスと 435 HEAD 435 435 435 CENTER FRONT FRONT 435 73% 2 435 F (SET/READ) TRUDER 432 435 757 435 DATE EXI BARREL TEMP 435 435 CENTER REAR CENTER 727 方 工ジ 8 工了 8 REAR PKE 375 375 333 350 203-562 10807 10807 E203-56-1 SAMPLE H ERRIMAN DENNISON W 30717955 30360013 LOT NUMBER 303178 DATA OPERATOR/ENGINEER WORK REQUEST NO 548444 36 548444 36 581051 30 581051 30 0.800 Kg 206 7930 150185 54KLYN Suk wat forting RESIN



BEST AVAILABLE COPY

EXHIBIT

BLOWN

Œ

0 C

ш

00

⋖

!-4

Z

EXTRUSIO

ドー Air Temp + Amt Chilled d L 55% 3570 3390 3150 3950 3530 2560 4 3 が 7 フ 9-297-27 SCREW SPEED RPM X6 1900 CESIER (C) 8 3 0 3 3 HEIGHT ANGLE TOWER SCREW MELT Femp. °F 200 DIE 367 3 J C 410 三丁 433 25 5 757 252 S P W **TOP** F (SET/READ) CENTER 5 35 3 3 DAVIS <u>1</u> 160 <u>구</u> Bottom 3 TEMP. 7(12) 7. 3. 3 OE NECK 557 55 5 760 150 35 Adaptor Q3)-250 30,7 9 35 5 <u>1</u> CENTER FRONT HEAD 3 752 3 3 5 BARREL TEMP. *F (SET/READ) 450 450 五百万 3 3 3 5 3 3 3 3 DATE 390 390 390 390 356 390 CENTER CENTE 390 **%** 37, 3 3 <u>~</u> 3 350 350 350 350 350 REAR 340 350 J <u>;</u> E-229-41 6-14-8ec 3 SAMPLE E229-41. E 229-41 5 DENNISON LOT DATA OPERATOR/ENGINEER Weter that a Davas Jana C W. Clerk , welex Shed? WORK REQUEST NO. SUPERVI HIZZIO KT2010 フュア SIRVA NUIS 137 3 Surves 160 TYPE RESIN Sugar Sicor くないばんなく Svery LES TRUTTE DE LE PROPERTIE DE LA COMPTENSIÓN DE LA COMPTENSIÓN DE LA COMPTENSIÓN DE LA COMPTENSIÓN DE LA COMPT